# Rotational effects associated with ground motion during the $M_w$ 6.3 2009 L'Aquila (central Italy) earthquake

C. CASTELLANO, L. CUCCI, A. TERTULLIANI and G. PIETRANTONIO Istituto Nazionale di Geofisica e Vulcanologia, Rome, Italy

(Received: March 24, 2011; accepted: July 14, 2011)

**ABSTRACT** The  $M_w$  6.3 2009 L'Aquila (central Italy) earthquake produced more than one hundred rotational effects on chimneys, pillars, capitals and gravestones. In this paper we focus on the 37 objects that can be more reliably considered as representative of pure rotational ground motion, and find a relation between the distribution of the observed rotations, the epicentral distance, the macroseismic intensities and the directivity effects that characterize the L'Aquila event. We also find sound relationships between the type of observed rotations and the geophysical, geotechnical and geomorphological characteristics of the site of observation. In downtown L'Aquila we find: 1) a remarkable convergence between distribution of the rotations and of the damage; 2) 100% of the rotations occurred at sites characterized by high factors of amplification and poor geological setting; 3) the ground rotations are not strongly dependent on topographic effects. Finally, from quantitative analyses of GPS data we find that the effect of the seismic arrival on an individual vertical object retrieved rotated is an overall rotation with a substantially unpredictable direction.

Key words: directivity, rotational effects, L'Aquila earthquake.

## 1. Introduction

Seismic actions are generally developed in terms of translational ground motion, as the rotational counterparts of motion are mostly ignored. This is the consequence of the fact that earthquake-induced ground rotations have always been considered too small and too difficult to measure with accuracy. Conversely, such rotational effects, often regarded as a weird and astonishing phenomenon, have been known and were widely reported for centuries. The first significant instances of earthquake-induced rotational effects were provided by the M~7 1783 Calabria event and the M~7 1857 Great Neapolitan Earthquake, both occurred in southern Italy. In particular, the occurrence of the 1857 event allowed Mallet (1862) to formalize a number of mechanisms that satisfactorily explained the observed rotational motions in the near fault region of the M=7.8 San Francisco (Jenista, 1906-1907), M=6.9 1974 Izu (Yamaguchi and Odaka, 1974) and M=6.8 1988 Armenia (Yegian *et al.*, 1994) earthquakes. Finally, Sargeant and Musson (2009) provided a compendium of observations of rotational effects from low to moderate earthquakes occurred in the United Kingdom.

In this paper we describe some of the rotational effects associated with the 2009  $M_w$  6.3 L'Aquila earthquake (Fig. 1). The L'Aquila event occurred at about 9.5 km depth on the Paganica



Fig. 1 - Map of the study area (modified from Cucci and Tertulliani, 2011). The focal mechanism by Pondrelli *et al.* (2010) indicates the position of the epicentre of the 2009 L'Aquila earthquake. Aftershock distribution from ISIDe, the Italian Seismic Instrumental and Parametric Data-Base (http://iside.rm.ingv.it/iside/standard/index.jsp). A solid curved line encircles the area where earthquake-induced rotational effects (both building-based objects and free-field objects, see below in the main text) have been observed. Triangles mark the location of the two GPS stations CADO and ROIO. We also indicate the surface expression of the normal Paganica Fault (hachures on the hanging wall).

Fault (Vezzani and Ghisetti, 1998), a NW-trending, SW-dipping seismogenic source quite clearly defined by the seismicity distribution (Chiarabba *et al.*, 2009), the focal mechanism of the mainshock (Pondrelli *et al.*, 2010), the GPS and DinSar modelling (Anzidei *et al.*, 2009; Atzori *et al.*, 2009; Papanikolaou *et al.*, 2010), and the pattern of coseismic surface fractures (Boncio *et al.*, 2010; Emergeo Working Group, 2010).

The macroseismic survey of the 2009 earthquake (Galli *et al.*, 2009) showed that the largest damage was mainly distributed in a NW-SE direction and noticeably located SE of the instrumental epicentre, thus providing evidence of important directivity effects. During the macroseismic survey, we collected and classified an impressive number of rotational effects on buildings, monuments in villages and cemeteries and articles of furniture. The rotations affected more than one hundred vertically organized objects such as chimneys, pillars, capitals and gravestones.

Cucci and Tertulliani (2011) first presented the whole data set of rotational effects induced by the L'Aquila earthquake, finding a significant convergence between the distribution of the rotations and of the damage. They also put in evidence that some geological factors (lithology and site amplification) influence the rotational effects more than the seismological factors (slip distribution). In this work we try to establish more sound relationships between the type of



Fig. 2 - The sketch represents the two main typologies of rotations observable in the field: a) building-based object: chimney in Pianola (3 km from the epicentre), building-based objects like chimneys, furniture and some pillars are usually placed on top of a building or a construction and can be affected by rotational modes of the underlying structure; b) free-field object: pillar at the L'Aquila University (2 km from the epicentre), free-field objects like tombstones, gate pillars, capitals, monuments and some statues rest directly on the ground, are considered reliably representative of pure rotational ground motion, and constitute the data set of this work.

observed rotations and the geophysical, geotechnical and geomorphological characteristics of the site of observation. Also, we focus on the particular situation in downtown L'Aquila where the extension of the settlement does not allow us to consider it as a single site. Moreover, in order to assess if the earthquake induced a specific direction of rotation, we analyze high frequency data of two GPS stations located in the area where earthquake-induced rotational effects have been observed (Fig. 1).

## 2. Analyses of rotational effects

Past studies have emphasized the role played by a number of site and source effects in enhancing the earthquake-induced rotations. In particular, the changes of rupture velocity (Bouchon and Aki, 1982; Takeo and Ito, 1997), the local rheology (Huang, 2003; Spudich and Fletcher, 2008), and topographic effects (Stupazzini *et al.*, 2009) have been called for as important contributors to local rotations. However, in the analyses of the observed rotational effects sometimes it can be difficult to discriminate between true rotational motion and translational motion (Hinzen *et al.*, 2010). Asymmetrical distribution of mass and stiffness are quite common in buildings without anti-seismic design, and could cause rotational modes whose participating mass exceeds the one involved in translational modes. Rotational modes have also been observed at some given frequencies in a reinforced concrete building, explainable with irregularities and eccentricity in respect of the main geometrical axes (Mucciarelli *et al.*, 2011). In some cases, the rotation observed on a particular object can likely



Fig. 3 - Examples of ffd rotations observed following the L'Aquila earthquake.

derive from non-uniform frictions on its support. For this reason, starting from the two classes of rotational effects (free-field-based or building-based objects, see Fig. 2) suggested by Cucci and Tertulliani (2011), we focussed our analyses only on the free-field-based (ffd hereinafter) objects. Ffd objects like tombstones, gate pillars and monuments (Fig. 3) rest directly on the ground, are not affected by rotational modes of the underlying structure, and can be considered as representative of pure rotational ground motion. Therefore, the original data set with 105 observations at 37 different sites [see Table 1 in Cucci and Tertulliani (2011) for the full description of the whole data set] is now reduced to 37 effects observed at 15 localities. To check for correlation between distribution of ffd rotations and local geological pattern, we superimpose our data on a map (Fig. 4) prepared merging data from: i) the geological map by Vezzani and Ghisetti (1998), that provides the background geological information; ii) the seismic microzonation map by the Italian Civil Protection (http://www.protezionecivile.it/jcms/it/microzonazione\_aquilano.wp?toptab=1 - top-content), that shows the sites prone to amplification of the seismic signal on the bases of geomorphological observations and geotechnical prospections; and iii) a detailed geological survey of the sites of observations. On this basis the terrains are divided in two different classes according to their characteristics, either 'stable' (e.g., unfractured outcrops of



Fig. 4 - Distribution of ffd rotational effects induced by the L'Aquila earthquake and geological characteristics of the sites of observation (numbers in parenthesis indicate multiple observations associated to the same location). The terrains are divided in either 'stable' or 'not stable' according to their geophysical/geotechnical/geomorphological characteristics. Crossed circles indicate sites where rotational effects did not occur. A black star shows the location of the epicentre of the L'Aquila earthquake. Triangles mark the location of the two GPS stations CADO and ROIO.

limestone/flysch bedrock not affected by amplification) or 'not stable' (e.g., artificial landfills, fluvial and lacustrine deposits, alluvial fans, slope deposits, fractured/weathered bedrock with evidence of amplification) sites.

Fig. 4 and Table 1 show the results of the comparison between the distribution of ffd effects and the geological characteristics of the sites of observation. Two rotations out of 37 observations (5%) were observed on stable sites, 35 were observed on not stable sites (95%). Performing our calculations on the number of localities where at least one rotation was observed, we find that the not stable sites are 13 out of 15, the 87% of the total. We also checked the classification stable/not stable for all the other 33 sites, located in the near fault region, where rotational effects did not occur. In this case the occurrence provides percentage rates remarkably balanced between stable and not stable sites (48% and 52% respectively, Table 1).

	Number	Stable	Not stable
Observed rotations*	37	2 (5%)	35 (95%)
Sites with rotations†	15	2 (13%)	13 (87%)
Sites without rotations#	33	16 (48%)	17 (52%)

Table 1 - Comparison between observed rotational motions and geological characteristics of the site.

\* Data set of rotations: reports the total number of observations.

† Data set of rotations: reports the total number of localities with at least one rotation.

# Sites where rotational effects did not occur.

#### 3. Rotations observed downtown L'Aquila

A particular case we examine in this study is that of downtown L'Aquila, where severe damage occurred (intensity VIII-IX MCS) and where we retrieved many rotated objects. Within the historical centre of L'Aquila we observed 24 rotated objects, 15 of which are ffd. They are columns, pillars, statues, chimneys and ornamental marble blocks (Fig. 5) retrieved rotated after detailed surveys. The extension of the settlement and the fact that a remarkable number of rotations were observed in the old city required a more detailed approach in terms of geological/geomorphological survey and seismic microzonation. Therefore, we conveyed to Fig. 6 all the information available from the geology of the area (Gruppo di lavoro MS\_AQ, 2010) and from the map of the amplification factors (Milana *et al.*, 2011).

The historical centre of L'Aquila is settled on a fluvial terrace formed by Quaternary breccias ["Megabrecce" sensu Demangeot (1965)] of variable thickness and stiffness (Blumetti *et al.*, 2002). In the southern part of the city a formation of reddish silts [L'Aquila Red Silts (Gruppo di lavoro MS\_AQ, 2010)] outcrops over the marly breccias. The terrace is carved by fluvial incisions filled by colluvial deposits of limited thickness. Instrumental measurements of seismic noise and microtremors (De Luca *et al.*, 2005; Milana *et al.*, 2011) highlighted the presence of amplification of the ground motion throughout the historical centre, with particular emphasis in the areas where Red Silts outcrop. Amplification factors higher than 2 have been determined. Microzonation activities (Gruppo di lavoro MS\_AQ, 2010), performed during and after the 2009 sequence have also enlightened that the breccias do not continuously extend and are substituted in places by the Red Silts. Ground motion analyses confirmed that all the historical centre of L'Aquila is prone to local amplification, with amplification factors bigger in the area of the city where the Red Silts outcrop and where a velocity reversal due to geological conditions was demonstrated by Bordoni *et al.* (2011).

The analysis of the ground motion is in good agreement with the distribution of the damage, more severe in the Red Silts zone, and in general in the central and south-western parts of the city (Tertulliani *et al.*, 2011). In fact several total collapses of reinforced concrete buildings occurred in that area as opposed to the north-eastern sector of the city.

If we consider the trace of the watershed in the old town (represented by the main NNE-SSW street, see Fig. 6), all the rotations are placed in the western sector of the city where also the major damaged areas are located. It is interesting to note that within the downtown we retrieved several multiple observations (observations of rotated objects in the same place, for instance Palazzo



Fig. 5 - Examples of ffd rotations observed in downtown L'Aquila.

Camponeschi and San Pietro a Coppito square) with non-coherent directions of rotation (both clockwise and counter-clockwise, see Fig. 5). This observation would suggest that the direction of the rotation was not affected by any other factor than the frictions and the physical constraints of the object itself.

## 4. Rotation analysis by high frequency GPS data

Just a few days before the  $M_w$  6.3 earthquake, five GPS stations acquiring data at different

sampling rates (30 s, 1 s and 0.1 s) were installed in the epicentral area; these stations recorded the mainshock and permitted to properly resolve the near-field coseismic deformation pattern (Anzidei *et al.*, 2009).

The GPS monuments can be rightly considered as ffd objects since they are concrete pillars funded on limestone outcrops and not installed on buildings. In order to deeply investigate if the earthquake triggered a specific direction of rotation, at least for this kind of objects, here we considered data at the highest available frequency (10 Hz) of GPS stations CADO and ROIO, both located in the area where earthquake-induced rotational effects have been observed (Fig. 1).

We started from the horizontal components of motion (east, north) at CADO and ROIO in a topocentric Cartesian reference frame (Serpelloni *et al.*, 2009), relating to a few minutes around the mainshock epoch (1:32:40 UTC). For each observation epoch (sampling 0.1 s) we calculated the signed curvature of the planar trajectory, defined as

$$k = \frac{\dot{x}\ddot{y} - \dot{y}\ddot{x}}{\left(\dot{x}^2 + \dot{y}^2\right)^{3/2}}$$
(1)

where  $\dot{x}$ ,  $\dot{y}$  and  $\ddot{x}$ ,  $\ddot{y}$  are the first and second time derivatives of the two horizontal components x and y (in our case east and north), respectively. The sign of the signed curvature k indicates the direction in which the tangent vector rotates: if it rotates counter-clockwise, then k > 0, if it rotates clockwise, then k < 0.

The absolute value of k is the reciprocal of the radius of curvature R, i.e., the radius of the osculating circle to the trajectory

$$|k| = \frac{1}{R}.$$
(2)

The computed curvatures of the two GPS planar trajectories turn out to be very noisy and to constantly change their sign, thus indicating continuous variations in the direction of the rotation (from clockwise to counter-clockwise and viceversa). Figs. 7a and 7b show the 10 Hz-time series of the east and north components and a moving average of the curvature (used to partly smooth out short-term fluctuations) for the two GPS sites, in the time span from 1:32:10 to 1:33:30 (UTC).

Despite the high background noise, it is nevertheless possible to highlight some particular features related with the earthquake occurrence. At the first seismic arrivals (earlier at ROIO than at CADO as ROIO is closer to the epicentre) there are not large amplitude pulses at both GPS stations and both the corresponding curvatures do not show particular variations in their behaviours, keep being noisy, with large values (corresponding to little curvature radii), and constantly changing sign.

The large amplitude portion of GPS signals [which cannot be modelled as a source effect, but probably as a fault zone resonance (Avallone *et al.*, 2010)] occurs about 5 s after the beginning of the deformation at each site and spans about 7 s (Avallone *et al.*, 2011); in this time span the



Fig. 6 - Distribution of the ffd rotational effects, geology and amplification factors in downtown L'Aquila. Circles mark the sites of the observed rotations (numbers inside the circles indicate multiple observations associated to the same location). Differently grey shaded areas represent the main geological outcrops in the old town [simplified from Gruppo di lavoro MS\_AQ (2010)]. Legend: Ba, breccias of L'Aquila (middle Pleistocene); Lr, red silts (middle-upper Pleistocene); Fd, fluvial and colluvial deposits (upper Pleistocene-Holocene). Squares indicate the AF evaluated from aftershocks in the 2-10 Hz range by Milana *et al.* (2011). A black curve separates the area of more severe damage localized SW in the map. A dashed line marks the local watershed.



Fig. 7 - 10-Hz time series of the east and north components (top) and curvature (moving average) (bottom) for the two GPS sites, CADO (a) and ROIO (b), in the time span from 1:32:10 to 1:33:30 (UTC) of April 6, 2009.

curvatures seem to change their trend: values suddenly become close to zero, indicating almost infinite curvature radii, i.e., straight trajectories.

High frequency GPS data seem to highlight that the first seismic arrivals did not induce

rotations with a well-defined direction, whilst they put in evidence that the following large amplitude effects probably triggered a rectilinear motion. Likely, the resulting effect on ffd objects is an overall rotation with an unpredictable direction.

### 5. Discussion and conclusions

The first main purpose of this paper was to check whether and how some geophysical observables influence a number of objects retrieved rotated following the 2009 L'Aquila earthquake. To this aim, we preferred to reduce the original data set investigated by Cucci and Tertulliani (2011) from about 105 to 37 rotational effects (ffd rotations) more reliably affected by pure ground rotational motion. The analysis of our data confirms and corroborates a series of distinctive features of the L'Aquila earthquake-induced rotations that were first glimpsed by Cucci and Tertulliani (2011) with the large data set. The relationship between the distribution of the observed rotations, the epicentral distance, the macroseismic intensities and the directivity effects are further put in evidence when referred to ffd-type objects. As a matter of fact, the great majority of the ffd rotations are located in the epicentral area (within ~20 km from the instrumental epicentre) and where the intensity is between VII and VIII-IX MCS. Moreover, the evident asymmetry in the distribution of the ffd rotations (observed only SE of the epicentre) closely resembles the SE-ward directivity of the macroseismic effects.

As for the geological and seismological parameters that can influence the occurrence and the distribution of the rotational effects, Cucci and Tertulliani (2011) already put in evidence that the relation between rotations and pattern of slip distribution on the fault plane is quite feeble, in particular for those objects that are potentially affected by rotational modes of the underlying structure. For this reason, we chose to focus on the geological aspects of the question. Actually, what was an absolute majority (82-83%) of data where the geological factors affect the site of observation in Cucci and Tertulliani (2011), now becomes an overwhelming majority of 95%. If we consider each locality as a single datum independently from the number of rotations observed (a very conservative choice that does not take into account the frequent case of multiple observations at a same site) this percentage is still 87%. Conversely, a quick look at the partition stable/not stable (48%/52%) of those sites where rotational effects did not occur further strengthens our results. The result of this first part of investigation is that scarce geophysical and/or geotechnical characteristics or unfavourable geomorphological conditions at the site deeply influence the occurrence of earthquake-induced rotations.

The second main purpose of this work was to verify if the same kind of investigations carried out at the scale of the mesoseismic area ( $\sim$ 500 km<sup>2</sup>) provide similar results when applied at the local scale as in the case of downtown L'Aquila ( $\sim$ 2 km<sup>2</sup>). Also in this case we find a remarkable convergence between distribution of the rotations and of the damage, as 14 rotational effects out of 15 are located in the southern and western most severely damaged part of the old town (Fig. 6). In addition, all the rotations are distributed west of the local watershed, that runs in a N-S direction and roughly divides the historical centre in two specular halves that are topographically very similar. From this observation we can deduce as a first order evidence that ground rotation is not strongly dependent on topographic effects, at least in the case of L'Aquila. Moreover, our studies in downtown L'Aquila emphasized the influence of bad characteristics of the terrain on the rotational effects, as 100% of the rotations occurred at sites classified 'not stable' and characterized by high factors of amplification and poor geological setting.

Finally, the third purpose of the paper was to find specific relationships between the direction of rotation and the site of observation, i.e., if the clockwise or counterclockwise sense of rotation observed is predictable at a certain site. The results of this first attempt of a quantitative analysis of the data confirm that the clockwise/counterclockwise datum cannot be reliably associated with any seismological observables, as already suggested by the inconsistent sense of rotation witnessed sometimes at a same site. Indeed, very high frequency GPS data seem to confirm that the earthquake did not bring about a particular direction of rotation on objects: this direction would not be affected by any other factor than the frictions and physical constraints of the object itself.

**Acknowledgements.** We want to thank R. Devoti and F. Riguzzi for fruitful discussions, and E. Serpelloni for having provided the high frequency time series of the GPS coordinates. We also thank A. Rebez and an anonymous reviewer for several suggestions that improved the paper.

#### REFERENCES

- Anzidei M., Boschi E., Cannelli V., Devoti R., Esposito A., Galvani A., Melini D., Pietrantonio G., Riguzzi F., Sepe V. and Serpelloni E.; 2009: Coseismic deformation of the destructive April 6, 2009 L'Aquila earthquake (central Italy) from GPS data. Geophys. Res. Lett., 36, L17307, doi: 10.1029/2009GL039145.
- Atzori S., Hunstad I., Chini M., Salvi S., Tolomei C., Bignami C., Stramondo S., Trasatti E., Antonioli A. and Boschi E.; 2009: *Finite fault inversion of DInSAR coseismic displacement of the 2009 L'Aquila earthquake (central Italy)*. Geophys. Res. Lett., 36, L15305, doi: 10.1029/2009GL039293.
- Avallone A., Marzario M., Cirella A., Piatanesi A., Rovelli A., Di Alessandro C., D'Anastasio E., D'Agostino N., Giuliani R. and Mattone M.; 2011: Very high rate (10 Hz) GPS seismology for moderate magnitude earthquakes: the case of the M<sub>w</sub> 6.3 L'Aquila (central Italy) event. J. Geophys. Res., 116, B02305, doi: 10.1029/2010JB007834.
- Avallone A., Rovelli A. and Ben-Zion Y.; 2010: *Trapped seismic fault zone energy recorded by a high-rate GPS station*. Eos Trans. AGU, Fall Meet. Suppl., Abstract T53C–2142.
- Blumetti A.M., Di Filippo M., Zaffiro P., Marsan P. and Toro B.; 2002: Seismic hazard of the city of L'Aquila (Abruzzo - Central Italy): new data from geological, morphotectonic and gravity prospecting analysis. Stud. Geol. Camerti, 1, 7-18.
- Boncio P., Pizzi A., Brozzetti F., Pomposo G., Lavecchia G., Di Naccio D. and Ferrarini F.; 2010: Coseismic ground deformation of the 6 April 2009 L'Aquila earthquake (central Italy, M<sub>w</sub> 6.3). Geophys. Res. Lett., 37, L06308, doi: 10.1029/2010GL042807.
- Bordoni P., Haines J., Milana G., Marcucci S., Cara F. and Di Giulio G.; 2011: Seismic response of L'Aquila downtown from comparison between 2D synthetics spectral ratios of SH, P-SV and Rayleigh waves and observations of the 2009 earthquake sequence. Bull. Earthquake Eng., 9, 761-781, doi: 10.1007/s10518-011-9247-5.
- Bouchon M. and Aki K.; 1982: Strain, tilt, and rotation associated with strong ground motion in the vicinity of earthquake faults. Bull. Seismol. Soc. Am., 72, 1717-1738.
- Chiarabba C., Amato A., Anselmi A., Baccheschi P., Bianchi I., Cattaneo M., Cecere G., Chiaraluce L., Ciaccio M.G., De Gori P., De Luca G., Di Bona M., Di Stefano R., Faenza L., Govoni A., Improta L., Lucente F.P., Marchetti A., Margheriti L., Mele F., Michelini A., Monachesi G., Moretti M., Pastori M., Piana Agostinetti N., Piccinini D., Roselli P., Seccia D. and Valoroso L.; 2009: *The 2009 L'Aquila (central Italy) M<sub>w</sub> 6.3 earthquake: main shock and aftershocks.* Geophys. Res. Lett., **36**, L18308, doi: 10.1029/2009GL039627.
- Cucci L. and Tertulliani A.; 2011: Clues for a relation between rotational effects induced by the M<sub>w</sub> 6.3 2009 L'Aquila (Central Italy) earthquake and site and source effects. Bull. Seismol. Soc. Am., **101**, 1109-1120, doi: 10.1785/0120100264.

- De Luca G., Marcucci S., Milana G. and Sanò T.; 2005: Evidence of low-frequency amplification in the city of L'Aquila, Central Italy, through a multidisciplinary approach including strong- and weak- motion data, ambient noise, and numerical modeling. Bull. Seismol. Soc. Am., 95, 1469–1481, doi: 10.1785/0120030253.
- Demangeot J.; 1965: *Géomorphologie des Abruzzes Adriatiques*. Mémoires et Documents du C.N.R.S., Paris, France, 403 pp.
- Emergeo Working Group; 2010: Evidence for surface rupture associated with the  $M_w$  6.3 L'Aquila earthquake sequence of April 2009 (central Italy). Terra Nova, **22**, 43–51, doi: 10.1111/j.1365-3121.2009.00915.x.
- Galli P, Camassi R., Azzaro R., Bernardini F., Castenetto S., Molin D., Peronace E., Rossi A., Vecchi M. and Tertulliani A.; 2009: Terremoto de L'Aquila del 6 aprile 2009: distribuzione delle intensità macrosismiche ed implicazioni sismotettoniche. Il Quaternario, 22, 235-246.
- Gruppo di Lavoro MS\_AQ; 2010: La microzonazione sismica per la ricostruzione dell'area aquilana. Protezione Civile Roma, Italy, 3 vol. + 1 DVD.
- Hinzen K.G., Schreiber S. and Yerli B.; 2010: The Lycian sarcophagus of Arttumpara, Pinara, Turkey: testing seismogenic and anthropogenic damage scenarios. Bull. Seismol. Soc. Am., 100, 3148–3164, doi: 10.1785/0120100079.
- Huang B.S.; 2003: Ground rotational motions of the 1999 Chi-Chi, Taiwan, earthquake as inferred from dense array observations. Geophys. Res. Lett., **30**, 1307, doi: 10.1029/2002GL015157.
- Jenista J.; 1906-1907: O seismometrech. Vynélezy a Pokroky, III, Prague, pp. 10-164 (in Czech, On seismometers).
- Mallet R.; 1862: Great Neapolitan Earthquake of 1857: the first principles of observational seismology as developed in the Report to the Royal Society of London of the expedition made by command of the Society into the interior of the Kingdom of Naples to investigate the circumstances of the great earthquake of December 1857. Chapman and Hall, London, U.K., 2 volumes, 399 pp.
- Milana G., Azzara R.M., Bergamaschi F., Bertrand E., Bordoni P., Cara F., Cogliano R., Cultrera G., Di Giulio G., Duval A.M., Fodarella A., Marcucci S., Pucillo S., Régnier J. and Riccio G.; 2011: *The contribution of seismic data in microzonation studies for downtown L'Aquila*. Bull. Earthquake Eng., 9, 741-759, doi: 10.1007/s10518-011-9246-6.
- Mucciarelli M., Bianca M., Ditommaso R., Gallipoli M.R., Masi A., Milkereit C., Parolai S., Picozzi M. and Vona M.; 2011: Far field damage on RC buildings: the case study of Navelli during the L'Aquila (Italy) seismic sequence. Bull. Earthquake Eng., 9, 263–283, doi: 10.1007/s10518-010-9201-y.
- Papanikolaou I.D., Foumelis M., Parcharidis I., Lekkas E.L. and Fountoulis I.G.; 2010: Deformation pattern of the 6 and 7 April 2009, M<sub>w</sub>=6.3 and M<sub>w</sub>=5.6 earthquakes in L'Aquila (Central Italy) revealed by ground and space based observations. Nat. Hazards Earth Syst. Sci., 10, 73-87.
- Pondrelli S., Salimbeni S., Morelli A., Ekström G., Olivieri M. and Boschi E.; 2010: Seismic moment tensors of the April 2009, L'Aquila (Central Italy), earthquake sequence. Geophys. J. Int., 180, 238-242, doi: 10.1111/j.1365-246X.2009.04418.x.
- Sargeant S.L. and Musson R.M.W.; 2009: Rotational earthquake effects in the United Kingdom. Bull. Seismol. Soc. Am., 99, 1475-1479, doi: 10.1785/0120080097.
- Serpelloni E., Devoti R. and Cavaliere A.; 2009: *Analysis of high-rate GPS data collected during the L'Aquila sesmic sequence*. In: 28° Convegno Nazionale GNGTS, Riassunti estesi delle comunicazioni, Stella, Trieste, pp. 69-70.
- Spudich P. and Fletcher J.B.; 2008: Observation and prediction of dynamic ground strains, tilts, and torsions caused by the M<sub>w</sub> 6.0 2004 Parkfield, California, earthquake and aftershocks, derived from UPSAR array observations. Bull. Seismol. Soc. Am., 98, 1898-1914, doi: 10.1785/0120070157.
- Stupazzini M., de la Puente J., Smerzini C., Käser M., Igel H. and Castellani A.; 2009: Study of rotational ground motion in the near-field region. Bull. Seismol. Soc. Am., 99, 1271-1286, doi: 10.1785/0120080153.
- Takeo M. and Ito H.M.; 1997: *What can be learned from rotational motions excited by earthquakes?* Geophys. J. Int., **129**, 319-329, doi: 10.1111/j.1365-246X.1997.tb01585.x.
- Tertulliani A., Arcoraci L., Berardi M., Bernardini F., Camassi R., Castellano C., Del Mese S., Ercolani E., Graziani L., Leschiutta I., Rossi A. and Vecchi M.; 2011: An application of EMS98 in a medium-sized city: the case of L'Aquila (Central Italy) after the April 6, 2009 M<sub>w</sub> 6.3 earthquake. Bull. Earthquake Eng., 9, 67-80, doi: 10.1007/602 s10518-010-9188-4.

Vezzani L. and Ghisetti F.; 1998: Carta Geologica dell'Abruzzo, scala 1:100.000. S.EL.CA., Firenze.

Yamaguchi R. and Odaka T.; 1974: Field study of the Izu-Hanto-oki earthquake of 1974. Special Bull. Earthquake Res.

Inst., Univ. Tokyo, Japan, 14, 241-255.

Yegian M.K., Ghahraman V.G. and Gazetas G.; 1994: 1988 Armenia earthquake. II: damage statistics versus geologic and soil profiles. J. Geotech. Eng., 120, 21-45.

Corresponding author: Andrea Tertulliani Istituto Nazionale di Geofisica e Vulcanologia Via di Vigna Murata 605, 00143 Roma, Italy Phone: +39 06 51860219; fax: +39 06 51860507; e-mail: tertulliani@ingv.it